



REDOIL

TECHNICAL DATA SHEET



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

MULTIAGRI SAE 15W-40

Engine lubricant for agricultural and earthmoving machinery

SPECIFICS

API CJ-4/CI-4+/CI-4/CH-4 ACEA E7/E5
DTFR15B120 (MB 228.5) DTFR 15B110 (228.3)
MAN 3275-1 CATERPILLAR ECF-2 /ECF-A
MTU Type 3 -OIL TYPE 2 Deutz DQC IV-10
CUMMINS CES 20078 JASO FH-1
VOLVO VDS-3 RENAULT RVI RLD-2
Mack EO-N / EO-M / EO-M PLUS
SFU IVECO DH-1 18-1804 T2 E7



TECHNICAL DESCRIPTION

Special multigrade full-ash lubricant designed for agricultural transport vehicles and earth-moving machinery operating in extremely harsh and prolonged conditions. The high-density formulation is a highly valued solution for professionals when the type of lubricant recommended by the manufacturer is insufficient to handle particularly demanding load conditions. The premium synthetic technology formulation provides excellent stability, reducing oxidation phenomena even when operating temperatures in turbocharged systems equipped with turbochargers become particularly high. The inclusion of high-SAPS HS dispersant, anti-sludge, anti-foam, and detergent additives enables optimal protection, enhanced performance, and extended oil change intervals.

The use of this product ensures the following benefits:

- Sealing action
- Maximum oxidative stability
- Neutralisation of acids
- Protection against deposits, varnish, and sludge
- Maximum thermal stability
- Extended oil change intervals
- Maximum detergency
- Excellent dispersant, anti-corrosion, and anti-rust properties

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL

TECHNICAL DATA SHEET

MULTIAGRI SAE 15W-40



EELQMS

Data di prima emissione: 19/11/2023
19/11/2023
MANAGEMENT SYSTEM
Rev. N°4 del 01/07/2024

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,88
Viscosity 40°C	cSt	ASTMD445	110
Viscosity 100°C	cSt	ASTMD445	15
Viscosity Index	-	ASTMD2270	142
Flash Point	°C	ASTMD92	236
Freezing point	°C	ASTMD97	-26

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio